



CUSHMAN®

SHUTTLE™ 4



MOVE PEOPLE AND GEAR WITH EASE.

Specifically designed to multi-task, the Shuttle™ 4 combines four-forward facing seats and a spacious cargo bed, ready to transport people and equipment from every corner of your facility. Available as an energy efficient, 72V AC electric drivetrain or a 13.5 hp EFI gas engine the Shuttle 4 has plenty of power and range to tackle your most demanding days.

LET'S WORK.®

**13.5HP
EFI GAS**

**72V
AC ELECTRIC
DRIVETRAIN**

**1200LB
TOTAL LOAD
CAPACITY**



CUSHMAN® SHUTTLE™ 4



HEADLIGHTS



BENCH SEATING

RACK-AND-PINION
STEERING

OPTIONS & ACCESSORIES

- Rearview Mirror
- Windshield
- Canopy
- Hour Meter
- Individual Key Switch
- Pinstripes
- Body Color (Forest Green, White or Custom Options)
- On Board Charger
- Turn Signal with Four-Way Flashers
- Brakelights
- LED Headlights
- CE Kit (gas only)
- Wheel Covers
- Limited Slip Differential
- Trail Tires



COVERED WITH THE 2-YEAR CUSHMAN CARE TOTAL PROTECTION WARRANTY

ELECTRIC MODEL

EFI GAS MODEL

BODY & CHASSIS	
FRAME	Welded Steel w/ DuraShield™ Powder Coat
BODY & FINISH	Injection Molded TPO
STANDARD COLOR	Patriot Blue
DIMENSIONS	
OVERALL LENGTH	133.5 in (339 cm)
OVERALL WIDTH	48.5 in (123 cm)
OVERALL HEIGHT	48.6 in (123 cm) (w/o Roof) / 72.0 in (183 cm) (w/ Struts & Roof)
WHEEL BASE	93.5 in (237 cm)
WHEEL TRACK	34.2 in (87 cm) Front / 38.0 in (97 cm) Rear
GROUND CLEARANCE	4.3 in (11 cm)
CARGO DECK CAPACITY	9 cu ft (.25 m³)
CARGO DECK MATERIAL	Wood Stake Sides
POWER	
POWER SOURCE	72V DC
VALVE TRAIN	N/A
HORSEPOWER (KW)	22.4HP (16.7 kW) Intermittent
ELECTRICAL SYSTEM	72V
BATTERY (QTY/TYPE)	Six, 12 Volt Deep Cycle
BATTERY CHARGER	1000 Watt, 72V, 120/230V VAC UL Listed
KEY OR PEDAL START	Pedal
AIR CLEANER	N/A
LUBRICATION	N/A
OIL FILTER	N/A
COOLING SYSTEM	N/A
FUEL CAPACITY	N/A
SPEED CONTROLLER	350 Amp AC
DRIVE TRAIN	Motor Shaft Direct Drive
TRANSAXLE	Differential w/ Helical Gears
GEAR SELECTION	Dash-Mounted Forward-Neutral-Reverse
REAR AXLE RATIO	17:1
PERFORMANCE	
SEATING CAPACITY	4-Person
WEIGHT W/O BATTERIES	926 lb (420 kg)
CURB WEIGHT	1418 lb (643 kg)
VEHICLE LOAD CAPACITY	1200 lb (544 kg)
BED LOAD CAPACITY	400 lb (181 kg)
OUTSIDE CLEARANCE CIRCLE	25.5 ft (7.8 m)
SPEED	16.5 mph ± 0.5 mph (26.4 kph ± 0.8 kph) (High Speed) 12 mph ± 0.5 mph (19.3 kph ± 0.8 kph) (Low Speed)
STEERING & SUSPENSION	
STEERING	Self-Compensating Rack & Pinion
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers
SERVICE BRAKE	Rear Wheel Mechanical, Self-Adjusting Drum
PARKING BRAKE	Self-Compensating, Single-Point Engagement
TIRES (FRONT & REAR)	18 x 8.50 - 8 (4 Ply Rated)

www.cushman.com

©2019 Textron Specialized Vehicles Inc.
Features and specifications of the vehicles are subject to change without notice.
Vehicle as photographed may include options not included on base model.

82283-G7 (Rev. 12/2018)