



CUSHMAN®

HAULER® 800X



MAKE TOUGH JOBS A WALK IN THE PARK.

Every part of the Cushman® Hauler® 800X utility vehicle is designed to take on tough jobs. From an 8.4-cubic-foot cargo bed, to bench seating, to a lifted suspension and trail tires, it can navigate off the beaten path without breaking a sweat. With the option of a fuel-efficient 13.5 hp EFI gas engine, or a quiet, zero-emissions 48V AC electric drivetrain, the power to boost performance is in your hands. It's time to see what utility really means. Take the Hauler 800X for a drive.

LET'S WORK.®

13.5 HP
EFI GAS

8.4 CU FT
CARGO BED

16.5 MPH
MAX SPEED

48V AC
ELECTRIC
DRIVETRAIN



CUSHMAN® HAULER® 800X



LIFTED SUSPENSION
W/ HIGH GROUND CLEARANCE



BED DIVIDERS

USB & 12V OUTLET

OPTIONS & ACCESSORIES

- Improved Surface Tires*
- Brake Lights*
- Taillights*
- Fuel/Oil Gauge (gas vehicle only)*
- On-board Charger (electric vehicle only)*
- Premium Steering Wheel*
- 2" Rear Receiver Hitch*
- LED Headlights with High/Low Beam
- ROPS-Certified Cab
- Bed Dividers
- Long-Handled Tool Holder
- Cargo Mesh Netting
- Weather Enclosure
- USB Outlet
- 12-Volt Outlet
- Canopy Storage Net
- Rearview Mirror
- Side body color

*Included in Commercial Package



COVERED WITH THE 2-YEAR CUSHMAN
CARE TOTAL PROTECTION WARRANTY

	ELECTRIC MODEL	EFI GAS MODEL
BODY & CHASSIS		
FRAME	Welded Steel w/ E-Shield e-coat plus DuraShield™ Powder Coat	
BODY & FINISH	Injection Molded TPO (Front) / Injection Molded PP (Rear)	
STANDARD COLOR	Patriot Blue	
DIMENSIONS		
OVERALL LENGTH	110 in (279.4 cm)	
OVERALL WIDTH	49 in (125 cm)	
OVERALL HEIGHT	51 in (129.5 cm) (w/o Roof) / 74 in (188 cm) (w/ Canopy)	
WHEEL BASE	65.5 in (166.4 cm)	
WHEEL TRACK	37 in (94.0 cm) Front / 38 in (96.5 cm) Rear	
GROUND CLEARANCE	5.5 in (14.0 cm)	
CARGO DECK CAPACITY	8.4 cu ft (0.24 m³)	
CARGO DECK DIMENSIONS	44.5 in x 28.5 in x 12 in (113 cm x 72 cm x 30.5 cm)	
CARGO DECK MATERIAL	Roto-Molded Polyethylene	
POWER		
POWERTRAIN	48V AC	4-Cycle, 24.5 ci (401cc)
VALVE TRAIN	N/A	Single Cylinder OHV
HORSEPOWER (KW)	4.4 hp (3.3 kW) Continuous	13.5 hp (10.1 kW)
ELECTRICAL SYSTEM	48V	Starter/Generator. Solid State Reg.
BATTERY (QTY/TYPE)	Six, 8V Deep Cycle	One, 12V Maintenance Free
BATTERY CHARGER	48V DC PowerWise QE, 120V AC, UL/CSA	N/A
KEY OR PEDAL START	Pedal	
AIR CLEANER	N/A	Replaceable Dry Cartridge
LUBRICATION	N/A	Pressurized Oil System
OIL FILTER	N/A	Spin-On
COOLING SYSTEM	N/A	Air Cooled
FUEL CAPACITY	N/A	5.96 Gallon (22.6 L)
SPEED CONTROLLER	235 Amp AC Controller	N/A
DRIVE TRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission
TRANSAXLE	Differential w/ Helical Gears	
GEAR SELECTION	Dash-Mounted Forward-Neutral-Reverse	Forward - Reverse
REAR AXLE RATIO	16.99: 1	11.47: 1 (Forward) 14.53: 1 (Reverse)
PERFORMANCE		
SEATING CAPACITY	2-Person (Bench)	
WEIGHT W/O BATTERIES	756 lb (342.9 kg)	800 lb (362.9 kg)
CURB WEIGHT	1122 lb (508.9 kg)	830 lb (376 kg)
VEHICLE LOAD CAPACITY	725 lb (328.9 kg)	
BED LOAD CAPACITY	325 lb (147.4 kg)	
TOWING CAPACITY	500 lb (226.8 kg)	
OUTSIDE CLEARANCE CIRCLE	18.9 ft (5.8 m)	
SPEED	16.5 mph ± 0.5 mph (26.5 kph ± 0.8 kph)	
STEERING & SUSPENSION		
STEERING	Self-Compensating Rack & Pinion	
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers	
SERVICE BRAKE	Rear Wheel Mechanical, Self-Adjusting Drum	
PARKING BRAKE	Self-Compensating, Single-Point Engagement	
TIRES (FRONT & REAR)	20 x 8-10 (6 Ply Rated)	

www.cushman.com

©2019 Textron Specialized Vehicles Inc. All rights reserved. Features and specifications of the vehicles are subject to change without notice. Vehicle as photographed may include options not included on base model.

82291-G6 (Rev. 12/2018)