



CUSHMAN®



HAULER® 1200X

GEARED UP FOR YOUR COURSE'S BIGGEST OBSTACLES.

With a no-nonsense attitude the new Hauler® 1200X is ready to attack your toughest work days. A ton of standard features include a lifted suspension, ergonomic seats and ample leg room that complement its smooth ride and rugged demeanor. From transporting equipment to watering down a parched green on a hot summer's day or spraying unruly weeds, the Hauler 1200X is a force to be reckoned with. When your work has infinite hours the Hauler 1200X has reliability you can count on.

LET'S WORK.®

13.5HP
KAWASAKI
GAS

900LB
LOAD
CAPACITY

12 CU FT
CARGO
BED



CUSHMAN® HAULER® 1200X



HIGHER GROUND CLEARANCE



SIDE FILL GAS TANK



LIGHTS & BRUSH GUARD



OPTIONAL ALUMINUM BED/POWER DUMP

OPTIONS & ACCESSORIES

- Limited Slip Differential
- 4-Wheel Mechanical Brakes
- 4-Wheel Hydraulic Brakes
- Locking Glove Box
- Glove Box Mat
- Floor Mount Attachment
- Windshield
- Canopy
- Power Dump
- Long Handled Tool Holders
- Radio Holder
- Interior Tool Hook
- LED Headlights - Hi/Low
- Taillights
- Brakelights
- Hubcaps
- Ball Hitch Receiver
- Comfort Grip Steering Wheel
- High Altitude Jetting
- Fuel Gauge
- Rearview Mirror
- 12-volt Outlet
- USB Port
- Unique Key Switch
- Hour Meter
- Body Color (Patriot Blue, Forest Green, Ivory, Bright White, Flame Red, Orange, Black, Almond, Matte Black, Safety Yellow, Metallic Charcoal)
- Weather Enclosure
- Cab
- Ball Cage
- ROPS

BODY & CHASSIS	
FRAME	Welded Steel with E-Shield™ e-coat plus DuraShield™ Powder Coat
BODY & FINISH	Injected Molded TPO
STANDARD COLOR	Forest Green
DIMENSIONS	
OVERALL LENGTH	119 in (302 cm)
OVERALL WIDTH	49.4 in (125.5 cm)
OVERALL HEIGHT W/ CANOPY	77 in (196 cm)
WHEEL BASE	77.5 in (196.85 cm)
FRONT WHEEL TRACK	38.0 in (97 cm)
REAR WHEEL TRACK	38.5 in (98 cm)
GROUND CLEARANCE	7 in (18 cm)
CARGO BOX CAPACITY	12 cu ft (0.34 m ³)
POWER	
POWER SOURCE	4-cycle, 24.5 ci (401cc) Cylinder
VALVE TRAIN	Single Cylinder OHV
HORSEPOWER (KW)	13.5 hp (10.1 kW) Exceeds SAE J1940 Std.
ELECTRICAL SYSTEM	Starter/Generator, Solid-State Regulator
BATTERY (QTY/TYPER)	One 12V Maintenance Free
KEY OR PEDAL START	Pedal
AIR CLEANER	Dry Cartridge
LUBRICATION	Pressurized Oil System
OIL FILTER	Spin-On
COOLING SYSTEM	Air Cooled
FUEL CAPACITY	6.0 Gallon (22.7 L) Tank
DRIVE TRAIN	Continuously Variable Transmission (CVT)
TRANSAXLE	Differential with Helical Gears
GEAR SELECTION	Forward-Reverse
REAR AXLE RATIO	11.42:1(Forward) 15.78:1(Reverse)
PERFORMANCE	
SEATING CAPACITY	2 Person
CURB WEIGHT	1003 lb (455 kg)
BED LOAD CAPACITY	500 lb (227 kg)
VEHICLE LOAD CAPACITY	900 lb (408 kg)
SPEED	16.5 mph +/- 0.5 mph (26.6 kph +/- 0.8 kph)
TOWING CAPACITY	1200 lb (544 kg) max
OUTSIDE CLEARANCE CIRCLE	23.5 ft (7.16 m)
STEERING & SUSPENSION	
STEERING	Self-Compensating Rack and Pinion
FRONT/REAR SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers
SERVICE BRAKE	Rear Wheel Mechanical Self-adjusting Drum
PARKING BRAKE	Self-compensating, Single Point Engagement
FRONT/REAR TIRES	20 x 8.00 -10