



CUSHMAN

MODEL: HAULER 1200
TYPE: GASOLINE POWERED TRUCK
MODEL YEAR: 2017
Part No: 651387G01



PRODUCT SPECIFICATION

CONFIGURATION HIGHLIGHTS

Engine: 13.5 hp (10.1 kW) Exceeds SAE J1940 Standard, 4 cycle, 24.5 ci (401 cc) single cylinder, air-cooled by Kawasaki

- **Valve Train:** Overhead valve
- **Lubrication:** Pressurized oil system, spin-on oil filter
- **Balancer:** Internal counter rotating balance shaft
- **Fuel System:** Fixed float bowl with remote pulse fuel pump
- **Ignition:** Electronic spark/magneto
- **Air Cleaner:** Replaceable dry cartridge

Electrical: Starter/Generator, solid-state regulator, 12 Volt maintenance free battery (425 CCA, 60 minute reserve)

Drive Train: Automatic, continuously variable transmission (CVT)

Brakes: Dual rear wheel mechanical self-adjusting drum brakes. Automatic single point park brake release with self-compensating system.

Transaxle: Differential with helical gears, ground speed governor, forward/reverse

Cargo Bed: Roto-molded cross-linked polyethylene. Lifts for access to powertrain. Removable hinged multi-position tailgate with cam over latch mechanism.

PRODUCT OVERVIEW

Dimensions	
Overall Length	115.0 in (292.10 cm)
Overall Width	49.4 in (125.48 cm)
Overall Height (No Canopy)	47.3 in (120.14 cm) (Top of steering wheel)
Overall Height (With Canopy)	70.5 in (179.07 cm)
Wheel Base	76.8 in (195.07 cm)
Front Wheel Track	35.0 in (88.90 cm)
Rear Wheel Track	38.5 in (97.79 cm)
Gnd Clearance @ Differential	3.5 in (8.89 cm)
Cargo Box Width (inside)	44.0 in (111.76 cm)
Cargo Box Length (inside)	39.0 in (99.06 cm)
Cargo Box Depth (inside)	12.0 in (30.48 cm)
Cargo Box Capacity	12 cu ft (0.34 cu m)
Cargo Box material	Roto-molded polyethylene

Vehicle Power	
Power Source	4 Cycle 24.5 cu in (401 cc)
Valve Train	Single Cylinder OHV
Horsepower (kW)	13.5 hp (10.1 kW) Exceeds SAE J1940 Std.
Electrical System	Starter/Generator. Solid State Regulator
Batteries (Qty, Type)	One, 12 Volt Maintenance Free
Key or Pedal Start	Pedal
Air Cleaner	Replaceable Dry Cartridge
Lubrication	Pressurized Oil System
Oil Filter	Spin-On
Cooling System	Air Cooled
Max Fuel Volume	6.0 Gallon (22.7 L) tank
Drive Train	Continuously variable transmission (CVT)
Transaxle	Differential with helical gears
Gear Selection	Forward - Reverse
Rear Axle Ratio	11.42:1 (Forward) 15.78:1 (Reverse)

Performance	
Seating Capacity	2 Persons
Dry Weight	940 lb (426.38 kg)
Curb Weight	980 lb (444.52 kg)
Bed Load Capacity	800 lb (362.87 kg)
Vehicle Load Capacity	1200 lb (544.31 kg)
Outside Clearance Circle	21.5 ft (7.01 m)
Intersecting Aisle Clearance	N/A
Speed (Level Ground)	FWD - 14.5 mph ± 0.5 mph (23.34 kph ± 0.80 kph) Rev - 11.6 mph ± 0.5 mph (18.67 kph ± 0.80 kph)
Maximum Drawbar	720 lb (3203 N)
Towing Capacity	1500 lb (680.39 kg) max load

Steering & Suspension	
Steering	Self-compensating rack and pinion
Front Suspension	Leaf springs with hydraulic shock absorbers
Rear Suspension	Leaf springs with hydraulic shock absorbers
Service Brake	Rear wheel mechanical self-adjusting drum
Parking Brake	Self-compensating, single point engagement
Front Tires	K500 18 x 8.5 - 8 (6 Ply), Black Wheel
Rear Tires	K500 18 x 8.5 - 8 (6 Ply), Black Wheel

Body & Chassis	
Frame	Welded steel with DuraShield™ powder coat
Front Body & Finish	Injection-Molded TPO
Rear Body & Finish	Injection-Molded TPO
Standard Color	Forest Green

Some items shown may be optional equipment



OPTIONS & FIELD INSTALLED ACCESSORIES (Installation not included)*

Item	Std	Opt	Fld
IMPROVED SURFACE TIRES:			
Loadstar 18.5 x 8.5 - 8 (8 Ply), Black Wheel		X	
Loadstar 20.5 x 8 - 10 (6 Ply), Black Wheel		X	
TURF TIRES:			
K500 18 x 8.5 - 8 (6 Ply), Black Wheel	X		
K500 20 x 8 - 10 (6 Ply), Black Wheel		X	
WHEEL COVERS:			
8" Black & Gold (Set of 4)		X	
8" Black & Silver (Set of 4)		X	
10" Silver Wheelcover (Set of 4)		X	
BODY COLORS:			
Forest Green	X		
Patriot Blue, Ivory, Bright White, Flame Red & Black		X	
Premium Colors		X	
SIDE DECAL COLORS:			
Matte Black	X		
Forest Green, Patriot Blue, Ivory, Bright White, Flame Red & Black		X	
		X	
SEAT COLORS:			
Gray	X		
Stone Beige, Black & Oyster		X	
VEHICLE ENHANCEMENTS:			
Fender Flare - Small		X	
Fender Flare - Large		X	
2 Wheel Mechanical Brakes	X		
4 Wheel Hydraulic Brakes		X	
Limited Slip Differential		X	
High Altitude Jetting 3 - 6K ft (900 - 1800 m)		X	
High Altitude Jetting 6K + ft (1800m +)		X	
Frame - E-Shield Enhanced Coating		X	
Brush Guard		X	
Comfort Grip Steering Wheel		X	
Scorecard Holder		X	
ELECTRICAL:			
Hour Meter		X	
Headlights	X		
LED Headlights		X	
Taillights		X	
Brake Lights		X	
Fuel/Oil Gauge		X	
12 Volt Outlet		X	
USB Outlet		X	
Unique Key Switch		X	
12 Volt Heavy Duty Battery		X	
TOWING, HAULING & STORAGE:			
Rear Receiver 2 in (5 cm)	X		
Ball Hitch 1 7/8 in (48 mm)		X	
Angle Hitch		X	
Clevis Hitch		X	
Drop Clevis Hitch		X	

Item	Std	Opt	Fld
Drop Angle Hitch		X	
Drop Ball Hitch 1 7/8 in (48 mm)		X	
Plastic Bed	X		
Flat Bed		X	
Aluminum Bed		X	
Electric Dump		X	
Glove Box Locking Door		X	
Glove Box Shelf		X	
PLASTIC BED ACCESSORIES:			
Bed Net (Pocket)			X
D-Ring Tie Down, Track Mount			X
Tailgate Long Handled Tool Holder			X
Bed Divider			X
ALUMINUM BED ACCESSORIES:			
D-Ring Tie Down, Track Mount			X
Elevated Long Handled Tool Holder			X
Bed Divider			X
Bed Cage/Hoop Rack			X
Ladder Rack & Hook Kit			X
Tie Bar Kit			X
Flexible Tool Clamp Kit			X
WEATHER PROTECTION, ENCLOSURES & CABS:			
Canopy - Black, Tan & Champagne Beige			X
Windshield Flat			X
Windshield Fold Down			X
Enclosure - Black, White & Tan			X
Cab Kit - ROPS Certified			X
Ball Cage Kit - ROPS Certified			X
Cab - Strobe Light			X
Cab - Work Light			X
OTHER ENHANCEMENTS:			
Canopy Storage Net (blow mold canopy required)			X
Mirror - Canopy mounted			X
Mirror - 5 Panel			X