



CUSHMAN



MODEL: HAULER 1200 X
TYPE: GAS POWERED TRUCK
MODEL YEAR: 2017
Part No: 651390G01

PRODUCT SPECIFICATION

CONFIGURATION HIGHLIGHTS

Engine: 13.5 hp (10.1 kW) Exceeds SAE J1940 Standard, 4 cycle, 24.5 ci (401 cc) single cylinder, air-cooled by Kawasaki

- **Valve Train:** Overhead valve
- **Fuel System:** Fixed float bowl with remote pulse fuel pump
- **Lubrication:** Pressurized oil system, spin-on oil filter
- **Ignition:** Electronic spark/magneto
- **Balancer:** Internal counter rotating balance shaft
- **Air Cleaner:** Replaceable dry cartridge

Electrical: Starter/Generator, solid-state regulator, 12 Volt maintenance free battery (425 CCA, 60 minute reserve)

Drive Train: Automatic, continuously variable transmission (CVT)

Brakes: Dual rear wheel mechanical self-adjusting drum brakes. Automatic single point park brake release with self-compensating system.

Transaxle: Differential with helical gears, ground speed governor, forward/reverse

Cargo Bed: Roto-molded cross-linked polyethylene. Lifts for access to powertrain. Removable hinged multi-position tailgate with cam over latch mechanism.

PRODUCT OVERVIEW

Dimensions

Overall Length	119.0 in (302.26 cm)
Overall Width	49.4 in (125.48 cm)
Overall Height (No Canopy)	53.0 in (134.62 cm) (Top of steering wheel)
Overall Height (With Canopy)	77.0 in (195.58 cm)
Wheel Base	77.5 in (196.85 cm)
Front Wheel Track	38.0 in (96.52 cm)
Rear Wheel Track	38.5 in (97.79 cm)
Gnd Clearance @ Differential	7.0 in (17.78 cm)
Cargo Box Width (inside)	44.0 in (111.76 cm)
Cargo Box Length (inside)	39.0 in (99.06 cm)
Cargo Box Depth (inside)	12.0 in (30.48 cm)
Cargo Box Capacity	12 cu ft (0.34 cu m)
Cargo Box Material	Roto-Molded Polyethylene

Vehicle Power

Valve Train	Single Cylinder OHV
Horsepower (kW)	13.5 hp (10.1 kW) Exceeds SAE J1940 Std.
Electrical System	Starter/Generator. Solid State Regulator
Batteries (Qty, Type)	One, 12 Volt Maintenance Free
Key or Pedal Start	Pedal
Air Cleaner	Replaceable Dry Cartridge
Lubrication	Pressurized Oil System
Oil Filter	Spin On
Cooling System	Air Cooled
Max Fuel Volume	6.0 Gallon (22.7 L) tank
Drive Train	Continuously variable transmission (CVT)
Transaxle	Differential with helical gears
Gear Selection	Forward - Reverse
Rear Axle Ratio	11.42:1 (Forward) 15.78:1 (Reverse)

Performance

Seating Capacity	2 Person
Dry Weight	963 lb (436.81 kg)
Curb Weight	1003 lb (454.95 kg)
Bed Load Capacity	500 lb (226.80 kg)
Vehicle load capacity	900 lb (408.23 kg)
Outside Clearance Circle	23.5 ft (7.16 m)
Intersecting Aisle Clearance	N/A
Speed (Level Ground)	16.5 mph ± 0.5 mph (26.58 kph ± 0.80 kph)
Maximum Drawbar	500 lb (2224 N)
Towing Capacity	1200 lb (544.31 kg) max load

Steering & Suspension

Front Suspension	Leaf springs with hydraulic shock absorbers
Rear Suspension	Leaf springs with hydraulic shock absorbers
Service Brake	Rear wheel mechanical self-adjusting drum
Parking Brake	Self-compensating, single point engagement
Front Tires	K500 20 x 8 - 10 (6 Ply), Black Wheel
Rear Tires	K500 20 x 8 - 10 (6 Ply), Black Wheel

Body & Chassis

Frame	Welded steel. DuraShield™ powder coat
Front Body & Finish	Injection-Molded TPO
Rear Body & Finish	Injection-Molded TPO
Standard Color	Forest Green

Some items shown may be optional equipment



CUSHMAN

OPTIONS & FIELD INSTALLED ACCESSORIES (Installation not included)*

Item	Std	Opt	Fld
IMPROVED SURFACE TIRES:			
Loadstar 20.5 x 8 - 10 (6 Ply), Black Wheel		X	
TURF TIRES:			
K500 20 x 8 - 10 (6 Ply), Black Wheel	X		
ALL TERRAIN TIRES:			
Terra Trac 23 x 10.5 - 12 (6 Ply), Polished Spoke Wheel		X	
Terra Trac 22 x 11 - 10 (6 Ply), Polished Spoke Wheel		X	
WHEEL COVERS:			
10" Silver Wheelcover (Set of 4)		X	
BODY COLORS:			
Forest Green	X		
Patriot Blue, Ivory, Bright White, Flame Red & Black		X	
Premium Colors		X	
SIDE DECAL COLORS:			
Matte Black	X		
Forest Green, Patriot Blue, Ivory, Bright White, Flame Red & Black		X	
		X	
SEAT COLORS:			
Gray	X		
Stone Beige, Black & Oyster		X	
VEHICLE ENHANCEMENTS:			
Fender Flare - Large	X		
2 Wheel Mechanical Brakes	X		
Limited Slip Differential		X	
High Altitude Jetting 3 - 6K ft (900 - 1800 m)		X	
High Altitude Jetting 6K + ft (1800m +)		X	
Frame - E-Shield Enhanced Coating		X	
Brush Guard		X	
Comfort Grip Steering Wheel		X	
Scorecard Holder		X	
ELECTRICAL:			
Hour Meter		X	
Headlights	X		
LED Headlights		X	
Taillights		X	
Brake Lights		X	
Fuel/Oil Gauge		X	
12 Volt Outlet		X	
USB Outlet		X	
Unique Key Switch		X	
12 Volt Heavy Duty Battery		X	
STORAGE, HAULING & TOWING:			
Rear Receiver 2 in (5 cm)	X		
Ball Hitch 1 7/8 in (48 mm)		X	
Angle Hitch		X	
Clevis Hitch		X	
Drop Clevis Hitch		X	
Drop Angle Hitch		X	

Item	Std	Opt	Fld
Drop Ball Hitch 1 7/8 in (48 mm)		X	
Plastic Bed	X		
Flat Bed		X	
Aluminum Bed		X	
Electric Dump		X	
Glove Box Locking Door		X	
Glove Box Shelf		X	
PLASTIC BED ACCESSORIES:			
Bed Net (Pocket)			X
D-Ring Tie Down Qty 4			X
Tailgate Long Handled Tool Holder			X
Bed Divider			X
ALUMINUM BED ACCESSORIES:			
D-Ring Tie Down, Track Mount			X
Elevated Long Handled Tool Holder			X
Bed Divider			X
Bed Cage/Hoop Rack			X
Ladder Rack & Hook Kit			X
Tie Bar Kit			X
Flexible Tool Clamp Kit			X
WEATHER PROTECTION, ENCLOSURES & CABS:			
Canopy - Black, Tan & Champagne Beige			X
Windshield Flat			X
Windshield Fold Down			X
Enclosure Colors - Black, White & Tan			X
Cab Kit - ROPS Certified			X
Ball Cage Kit - ROPS Certified			X
Cab - Strobe Light			X
Cab - Work Light			X
OTHER ENHANCEMENTS:			
Canopy Storage Net (blow mold canopy required)			X
Mirror - Canopy mounted			X
Mirror - 5 Panel			X
Front Basket Kit			X
Gun Mount - Floor Kit			X
Clays Car Kit			X