

UNMATCHED PRODUCTIVITY STARTS HERE.

The Hauler 800, now available with an ELiTE® lithium powertrain activated by Samsung SDI battery technology or with a fuel-efficient 13.5 hp EFI gas engine, powers through your toughest workdays. With a fully customizable cargo bed, highly functional dash and a broad range of accessories, Hauler 800 vehicles have everything you need to finish job after job.



8.4 CU FT

CARGO BED

900 LB

TOWING CAPACITY

800LB

VEHICLE LOAD CAPACITY

2 PASSENGER

SEATING

ZERO MAINTENANCE

ELITE LITHIUM BATTERY





ELITE LITHIUM POWERTRAIN

- Zero Maintenance Battery
- 5-Year Battery Warranty
- Lightweight Footprint
- Increased Efficiency
- Upgrade to 6.2 Triple Pack for Extended Range
- Multifunction SOC/Speedometer Gauge
- Automatic Park Brake
- Limited Slip Differential

OPTIONS & ACCESSORIES

- 4-Wheel Mechanical Brakes
- Locking Glove Box
- Bed Dividers
- Floor Mount Attachment
- Windshield
- Canopy
- Electric Bed Lift
- Long-Handled Tool Holders
- Radio Holder
- Cargo Mesh Netting
- LED Headlights
- LED Taillights/Brake Lights
- Rearview Mirror
- USB Port
- Unique Key Switch
- Side Body Color
- Weather Enclosure
- ROPS-Certified Cab
- Ball Cage
- Hubcaps
- Rear Receiver Hitch
- Hour Meter
- Limited Slip Differential
- Rapid On-Board Charger
- Fuel/Oil Gauge

CUSHMAN.COM

HAULER 800

BODY & CHASSIS

FRAME	Welded Steel with E-Coat & DuraShield™ Powder Coat	
BODY & FINISH	Injection Molded TPO	
STANDARD COLOR	Forest Green	

HAULER 800 ELITE

HAULER 800 GAS

DIMENSIONS

110 in (279.4 cm)		
49 in (125 cm)		
47 in (119.4 cm) (No Canopy) 69.5 in (176.5 cm) (w/ Struts & Roof)		
65.5 in (166.4 cm)		
37 in (94 cm) Front / 38 in (96.5 cm) Rear		
4.3 in (10.9 cm)		
8.4 cu ft (0.24 cu m)		
28.5 in (L) x 44.5 in (W) x 12 in (D) (72.4 cm x 113 cm x 30.5 cm)		
Roto-Molded Polyethylene		
	49 in (125 cm) 47 in (119.4 cm) (No Canopy) 69.5 in (176.5 cm) (w/ Struts & Roof) 65.5 in (166.4 cm) 37 in (94 cm) Front / 38 in (96.5 cm) Rear 4.3 in (10.9 cm) 8.4 cu ft (0.24 cu m) 28.5 in (L) x 44.5 in (W) x 12 in (D) (72.4 cm x 113 cm x 30.5 cm)	

POWER

POWER TRAIN	56.7V Li-Ion Battery	4-Cycle, 24.5 cu in (401cc)
VALVE TRAIN	N/A	Single Cylinder OHV
HORSEPOWER (KW)	11.7 hp (8.7 kW) Peak	13.5 hp (10.1 kW)
ELECTRICAL SYSTEM	48V Primary, 12V Auxiliary	Starter/Generator. Solid State Reg.
BATTERY (QTY/TYPE)	2.2 Elite - Single Pack	One, 12V Maintenance Free
KEY OR PEDAL START	Pedal	
AIR CLEANER	N/A	Replaceable Industrial Rated Dry Cartridge
LUBRICATION	N/A	Pressurized Oil System
OIL FILTER	N/A	Spin-On
COOLING SYSTEM	N/A	Air Cooled
FUEL CAPACITY	N/A	5.96 Gallon (22.6 L) tank
DRIVE TRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission
TRANSAXLE	Differential w/ Helical Gears	
GEAR SELECTION	Dash Mount Forward-Neutral- Reverse / Key Switch	Forward - Reverse
REAR AXLE RATIO	16.99:1	11.47: 1 (Forward) 14.35:1 (Reverse)

PERFORMANCE

SEATING CAPACITY	2-Person (Bench)		
WEIGHT W/O BATTERIES	753 lb (342 kg)	761 lb (345.2 kg)	
CURB WEIGHT	800 lb (363 kg)	791 lb (359 kg)	
VEHICLE LOAD CAPACITY	800 lb (362.9 kg)		
BED LOAD CAPACITY	400 lb (181.4 kg)		
TOWING CAPACITY	900 lb (408.2 kg)		
OUTSIDE CLEARANCE CIRCLE	18.9 ft (5.8 m)		
SPEED	16.5 mph ± 0.5 mph (26.5 kph ± 0.8 kph)	14.5 mph ± 0.5 mph (23.3 kph ± 0.8 kph)	

STEERING & SUSPENSION

PARKING BRAKE	Automatic Electro-Magnetic	Single-Point Engagement	
		Self-Compensating,	
SERVICE BRAKE	Rear Wheel Mechanical Self-Adjusting Drum		
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers		
STEERING	Self-Compensating Rack and Pinion		

TIRES (FRONT & REAR) 18 x 8.5 -8 (6 Ply Tires)

