

ELITE SERIES

EXPERIENCE SUPERIOR PERFORMANCE.

Reach the full potential of your workday with the Hauler PRO Series. With a zero-maintenance ELiTE lithium powertrain activated by Samsung SDI battery technology, the Hauler PRO Series has the power to get the job done, all while providing the benefits of zero-maintenance batteries and lower operational costs.




ZERO Maintenance

ELITE LITHIUM BATTERY

1500 LB / 1200 LB TOWING CAPACITY

1200 LB / 900 LB LOAD CAPACITY

12 CU FT CARGO BED







HAULER PRO ELITE

HAULER PRO-X ELITE

ELITE LITHIUM POWERTRAIN

- Zero Maintenance
- 5-Year Battery Warranty
- Lightweight Footprint
- Increased Efficiency
- Upgrade to 6.2 Triple Pack for Extended Range
- Standard Limited Slip Differential
- Standard Automatic Park Brake
- Multifunction SOC/Speedometer Gauge

OPTIONS & ACCESSORIES

- 4-Wheel Mechanical Brakes
- Locking Glove Box
- Bed Dividers
- Floor Mount Attachment
- Windshield
- Canopy
- Electric Bed Lift
- 15 cu-ft Aluminum Bed with L-Track System
- Long-Handled Tool Holders
- Radio Holder
- Cargo Mesh Netting
- LED Headlights
- LED Taillights/Brake Lights
- Ladder/Hoop Rack (Aluminum Bed Only)
- Rearview Mirror
- USB Port
- Unique Key Switch
- Side Body Color
- Weather Enclosure
- ROPS-Certified Cab
- Ball Cage
- Hubcaps
- Standard Rear Receiver Hitch
- Hour Meter
- Rapid On-Board Charger

HAULER® PRO / ELITE SERIES

HAULER PRO ELITE HAULER PRO-X ELITE

BODY & CHASSIS

FRAME	Welded Steel with E-Coat & DuraShield™ Powder Coat	
BODY & FINISH	Injection Molded TPO	
STANDARD COLOR	Forest Green	

DIMENSIONS

OVERALL LENGTH	119 in (302 cm)		
OVERALL WIDTH	49 in (125 cm)		
OVERALL HEIGHT W/CANOPY	70.5 in (179.1 cm)	77 in (196 cm)	
WHEEL BASE	76.8 in (195 cm)	77.5 in (196.9 cm)	
FRONT WHEEL TRACK	35 in (88.9 cm)	38.0 in (96.56 cm)	
REAR WHEEL TRACK	38.5 in (97.8 cm)		
GROUND CLEARANCE	4.3 in (11 cm)	5.5 in (14 cm)	
CARGO BOX CAPACITY	12 cu ft (0.34 cu m)		
CARGO BOX DIMENSIONS	39 in (L) x 44 in (W) x 12 in (D) (99 cm x 111.8 cm x 30.5 cm)		
CARGO BOX MATERIAL	Roto-Molded Polyethylene		

POWER

POWER SOURCE	56.7V Li-Ion Battery	
MOTOR TYPE	AC Induction	
HORSEPOWER (KW)	14.9 hp (11.1 kW)	
ELECTRICAL SYSTEM	48V Primary, 12V Auxiliary	
BATTERY (QTY/TYPE)	4.2 ELITE - Twin Pack	
BATTERY CHARGER	811 Watt World Charger	
KEY OR PEDAL START	Pedal	
DRIVE TRAIN	Motor Shaft Direct Drive	
TRANSAXLE	Limited-Slip Differential with Helical Gears	
SPEED CONTROLLER	350 Amp AC Controller	
GEAR SELECTION	Dash Mounted Forward-Neutral-Reverse / Key Switch	
REAR AXLE RATIO	16.99:1	

PERFORMANCE

SEATING CAPACITY	2-Person	
CURB WEIGHT	926 lb (420 kg)	971 lb (440 kg)
BED LOAD CAPACITY	800 lb (363 kg)	500 lb (227 kg)
VEHICLE LOAD CAPACITY	1200 lb (544 kg)	900 lb (408 kg)
SPEED	16.5 mph ± .05 mph (26.5 kph ± 0.8 kph)	
TOWING CAPACITY	1500 lb (680 kg) max	1200 lb (544 kg) max
OUTSIDE CLEARANCE CIRCLE	21.5 ft (6.6 m)	

STEERING & SUSPENSION

STEERING	Self-Compensating Rack & Pinion	
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers	
SERVICE BRAKE	Dual Rear Wheel Mechanical, Self-Adjusting Drum	
PARKING BRAKE	Automatic Electro-Magnetic	
TIRES (FRONT & REAR)	18 x 8.5 - 8 (6 - Ply Tires)	20 x 8-10 (6 - Ply Tires)



