11

THHEFT HHE

# SHUTTLE™ 8

## ELEVATE HIGH VOLUME TRANSPORTATION.

The Shuttle 8 is the ideal vehicle for transporting large groups of people throughout your facility with its six forward-facing seats and two rear-facing seats. With the option of a maintenance-free ELiTE lithium powertrain activated by Samsung SDI battery technology or a fuelefficient 13.5 hp EFI gas engine, the Shuttle 8 keeps guests and workers alike going.



=

HI

...

ELITE LITHIUM OR 13.5 HP EFI GAS

### AUTOMATIC PARK BRAKE (ELITE ONLY)

**1600 LB** VEHICLE LOAD CAPACITY

CUSHMAN

CUSHMAN.COM



#### **ELITE LITHIUM POWERTRAIN**

- Zero Maintenance
- 5-Year Battery Warranty
- Lightweight Footprint
- Increased Efficiency
- Upgrade to 6.2 Triple Pack for Extended Range
- Standard Limited Slip Differential
- Standard Automatic Park Brake

#### **OPTIONS & ACCESSORIES**

- Rearview Mirror
- Windshield
- Canopy
- Hour Meter
- Individual Key Switch
- Additional Body Colors
- Turn Signal with Four-Way Flashers
- LED Headlights
- LED Taillights/Brake Lights
- Additional Body Colors
- CE Kit (Gas Only)
- Rapid On-Board Charger (ELiTE Only)
- Upgrade to 6.2 Triple Pack for Extended Range (ELITE Only)

# SHUTTLE<sup>TM</sup> 8

BODY & CHASSIS	SHUTTLE 8 ELITE	SHUTTLE 8 GAS		
FRAME	Welded Steel with E-Coat & DuraShield™ Powder Coat			
BODY & FINISH	Injection	Molded TPO		
STANDARD COLOR	Patriot Blue			
DIMENSIONS				
OVERALL LENGTH	171.3 in	ı (435 cm)		
OVERALL WIDTH	49.6 in (126 cm)			
OVERALL HEIGHT	48.6 in (123 cm) (w/o Roof) / 76.0 in (193 cm) (w/ Struts & Roof)			
WHEEL BASE	125.0 ir	n (318 cm)		
WHEEL TRACK	35.2 in (90 cm) Fron	nt / 36.7 in (93 cm) Rear		
GROUND CLEARANCE	4.4 in (11 cm)	3.0 in (8 cm)		
CARGO DECK CAPACITY	400 lb (181 kg)			
POWER				
POWER SOURCE	56.7V Li-Ion Battery	4-Cycle, 24.5 cu in (401cc)		
VALVE TRAIN	N/A	Single Cylinder OHV		
HORSEPOWER (KW)	14.9 hp (11.1 kW) Peak	13.5 hp (10.1 kW)		
ELECTRICAL SYSTEM	48V Primary, 12V Auxiliary	Starter/Generator. Solid State Reg.		
BATTERY (QTY/TYPE)	Single, 56.7V max Li-Ion Compositi Module and Cell Module ("Twin Pack")	e One, 12V Maintenance Free		
BATTERY CHARGER	56.7V, 811W World Charger, 3M Charging Cord	N/A		
KEY OR PEDAL START	Pedal			
AIR CLEANER	N/A Replaceable Industri N/A Rated Dry Cartridge			
LUBRICATION	N/A	Pressurized Oil System		
OIL FILTER	N/A	Spin-On		
COOLING SYSTEM	N/A	Air Cooled		
FUEL CAPACITY	N/A	5.96 Gallon (22.6 L) Tank		
DRIVE TRAIN	Motor Shaft Direct Drive	Continuously Variable Transmissio		
TRANSAXLE	Limited-Slip Differential with Helical Gears	Differential w/ Helical Gears		
GEAR SELECTION	Dash Mount Forward-Neutral- Reverse / Key Switch	Forward - Reverse		
REAR AXLE RATIO	16.99:1	11.47: 1 (Forward) / 14.35:1 (Reverse		
PERFORMANCE				
SEATING CAPACITY	8-Person			
WEIGHT W/O BATTERIES	1215 lb (551 kg)	1225 lb (556 kg)		
CURB WEIGHT	1289 lb (585 kg)	1265 lb (574 kg)		
VEHICLE LOAD CAPACITY	1600 lb (726 kg)			
BED LOAD CAPACITY	400 lb (181 kg)			
OUTSIDE CLEARANCE CIRCLE	35 ft (10.7 m)			
	16.5 mph ± 0.5 mph 16 mph ± 0.5 mph (26 4 kph ± 0.8 kph) (26 kph ± 0.8 kph)			

STEER	ING &	SUSP	ENSIO	N

STEERING	Self-Compensating Rack and Pinion		
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers		
SERVICE BRAKE	Rear Wheel Mechanical Self-Adjusting Drum		
PARKING BRAKE	Automatic Electro-Magnetic	Self-Compensating, Single-Point Engagement	
TIRES (FRONT & REAR)	215 / 60 - 8 Tires (8 Ply Rated)		

(26.4 kph ± 0.8 kph)

#### CUSHMAN.COM

Features and specifications of the vehicles are subject to change without notice. Vehicle as photographed may include options not included on base model. California state law prohibits the sale of Model Year 2024 and later gas-powered carts. ©2023 Textron Specialized Vehicles Inc. 82305-G10 (Rev. 05/2023)



. (26 kph ± 0.8 kph)