

VERSATILITY COMMANDS THE DAY.

The newly redesigned Shuttle 2+2 is the ideal choice for transporting personnel and visitors. Comfortably seating up to four passengers with bench seats, the rear seat will also convert to a cargo deck. The Shuttle 2+2 is offered in your choice of a fuel-efficient 13.5-hp EFI gas engine or with an ELiTE lithium drivetrain powered by Samsung SDI lithium technology.

ELITE

ELITE® LITHIUM

13.5 HP

EFI GAS

2 OR 4-WHEEL

MECHANICAL BRAKE OPTIONS

LIFTED

AND

UNLIFTED

OPTIONS





ELITE LITHIUM POWERTRAIN

- Zero Maintenance Battery
- 5-Year Battery Warranty
- Lightweight Footprint
- Increased Efficiency
- Upgrade to 6.2 Triple Pack for **Extended Range**
- Automatic Park Brake
- Multifunction SOC/Speedometer Gauge
- Limited Slip Differential

OPTIONS & ACCESSORIES

- IntelliGauge™ (ELiTE Only)
- 4-Wheel Mechanical Brakes
- Contoured Seats
- LED Headlights, Taillights and **Brake Lights**
- Brush Guard
- Lockable Glove Box with Shelf and Molded Rubber Mats
- Flat DOT Windshield
- Fold-Down Windshield
- Weather Enclosure
- USB Outlet
- Rearview Mirror
- ELiTE Lithium 2.2, 4.2, or 6.2 Pack
- Rapid On-Board Charger
- Additional Body Colors
- · Limited Slip Differential

SHUTTLE 2+2

SHUTTLE 2+2 ELITE SHUTTLE 2+2 GAS 20" TIRES 18" TIRES 20" TIRES 18" TIRES

	ASS	

FRAME	Welde	d Steel with E-Coat &	DuraShield™ Powd	er Coat		
BODY & FINISH		Injection N	lolded TPO	•••••		
STANDARD COLOR	Patriot Blue					
DIMENSIONS						
OVERALL LENGTH	113 in (287 cm)					
OVERALL WIDTH	47 in (119 cm)					
OVERALL HEIGHT (W/ CANOPY)	76 in (193 cm)	80 in (203 cm)	76 in (193 cm)	80 in (203 cn		
OVERALL HEIGHT (W/O CANOPY)	48 in (122 cm)	52 in (132 cm)	48 in (122 cm)	52 in (132 cm		
WHEEL BASE	65.5 in (166 cm)					
WHEEL TRACK	37 in (94 cm) Front / 38 in (97 cm) Rear					
GROUND CLEARANCE	4.3 in (11 cm)	5.5 in (14 cm)	4.3 in (11 cm)	5.5 in (14 cm		
POWER						
POWER SOURCE	56.7V Li-I	on Battery	4-Cycle, 24.5 cu in (401cc)			
VALVE TRAIN	N/A		Single Cylinder OHV			
HORSEPOWER (KW)	11.7 hp (8.7 kW)		13.5 hp (10.1 kW)			
ELECTRICAL SYSTEM	48V Primary, 12V Auxiliary		Starter/Generator, Solid State Regulator			
BATTERY (QTY/TYPE)	2.2 Single, 56.7V Li-Ion Composite Module		One, 12V Maintenance Free			
BATTERY CHARGER	56.7V, 350W Domestic Charger, N/A 3M Charging Cord N/A					
KEY OR PEDAL START		Pe	dal	•		
AIR CLEANER	N/A		Industrial Rated Dry Filter			
LUBRICATION	N/A		Pressurized Oil System			
OIL FILTER	N/A		Spin-On			
COOLING SYSTEM	N/A		Air Cooled			
FUEL CAPACITY	N/A		5.96 Gallon (22.6 L) tank			
DRIVE TRAIN	Motor Shaft Direct Drive		Continuously Variable Transmissio (CVT)			
TRANSAXLE	Differential w/ Helical Gears					
GEAR SELECTION	Dash Mount Forward-Neutral-Reverse / Key Switch		Forward - Reverse			
REAR AXLE RATIO	16.99:1		11.47: 1 (Forward) / 14.35:1 (Reverse			
PERFORMANCE						
SEATING CAPACITY		4-Pe	rson	·		
WEIGHT W/O BATTERIES	743 lb (342 kg)	782 lb (351 kg)	872 lb (396 kg)	913 lb (414 kg		
CURB WEIGHT	790 lb (363 kg)	829 lb (372 kg)	902 (409 kg)	963 lb (437 k		
VEHICLE LOAD CAPACITY	800 lb (363 kg)					
OUTSIDE CLEARANCE CIRCLE	18.9 ft (5.76 m)					
SPEED		16.5 mph ± 0.5 mph	(26.5 kph ± 0.8 kph)	ı		
STEERING & SUSPI	ENSION					
STEERING	Self-Compensating Rack and Pinion					
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers					
SERVICE BRAKE	Dual Rear Wheel Mechanical Self-adjusting Drum					
PARKING BRAKE	Automatic Electro-Magnetic Self-Compensating, Single-Point Engagement					
TIRES (FRONT & REAR)	Hole-N-One Tires	K399, 205/65-10, 6 Ply	Hole-N-One Tires	K399, 205/65 6 Ply		

CUSHMAN.COM

