



SHUTTLE™ 2

DELIVER HARD WORK.

Move large materials around your facility with the Shuttle 2.

Utilize the 1,200 lb cargo capacity and a 20.9 square-foot cargo deck to move anything from lumber to luggage. The Shuttle 2 is available with an ELiTE lithium drivetrain powered by Samsung SDI technology or a 13.5 hp EFI gas engine, both offering sufficient power to get the job done.

ELiTE[®]
LITHIUM

ELiTE[®] LITHIUM

OR

13.5 HP

EFI GAS

**AUTOMATIC
PARK BRAKE**
(ELiTE ONLY)

1200 LB
VEHICLE LOAD CAPACITY

20.9 SQ FT
CARGO DECK CAPACITY



SHUTTLE 2

SHUTTLE 2 ELITE

SHUTTLE 2 GAS

BODY & CHASSIS

| | |
|----------------|--|
| FRAME | Welded Steel with E-Coat & DuraShield™ Powder Coat |
| BODY & FINISH | Injection Molded TPO |
| STANDARD COLOR | Patriot Blue |

DIMENSIONS

| | |
|------------------|---|
| OVERALL LENGTH | 141.0 in (358 cm) |
| OVERALL WIDTH | 48.5 in (123 cm) |
| OVERALL HEIGHT | 48.6 in (123 cm) (w/o Roof) / 72.0 in (183 cm) (w/ Struts & Roof) |
| WHEEL BASE | 93.5 in (237 cm) |
| WHEEL TRACK | Front 34.2 in (87 cm) / Rear 38.0 in (97 cm) |
| GROUND CLEARANCE | 4.3 in (11 cm) 3.9 in (9.8 cm) |
| CARGO DECK | 68 in (L) x 44.50 in (W) (172.65 cm x 113 cm) |

POWER

| | | |
|---------------------|---|---|
| POWER SOURCE | 56.7V Li-Ion Battery | 4-Cycle, 24.5 cu in (401cc) |
| VALVE TRAIN | N/A | Single Cylinder OHV |
| HORSEPOWER (KW) | 14.9 hp (11.1 kW) | 13.5 hp (10.1 kW) |
| ELECTRICAL SYSTEM | 48V Primary, 12V Auxiliary | Starter/Generator. Solid State Reg. |
| BATTERY (QTY/TYPER) | Single, 56.7V max Li-Ion Composite Module and Cell Module ("Twin Pack") | One, 12V Maintenance Free |
| BATTERY CHARGER | 56.7V, 811W World Charger, 3M Charging Cord | N/A |
| KEY OR PEDAL START | | Pedal |
| AIR CLEANER | N/A | Replaceable Industrial Rated Dry Cartridge |
| LUBRICATION | N/A | Pressurized Oil System |
| OIL FILTER | N/A | Spin-On |
| COOLING SYSTEM | N/A | Air Cooled |
| FUEL CAPACITY | N/A | 6 Gallon (22.7 L) Tank |
| DRIVE TRAIN | Motor Shaft Direct Drive | Continuously Variable Transmission |
| TRANSAXLE | Limited-Slip Differential with Helical Gears | Differential with Helical Gears |
| GEAR SELECTION | Dash Mount Forward-Neutral- Reverse / Key Switch | Forward - Reverse |
| REAR AXLE RATIO | 16.99:1 | 11.47:1 (Forward) / 14.35:1 (Reverse) |

PERFORMANCE

| | | |
|--------------------------|--|--|
| SEATING CAPACITY | 2-Person | |
| WEIGHT W/O BATTERIES | 810 lb (367 kg) | 884 lb (402 kg) |
| CURB WEIGHT | 923 lb (419 kg) | 926 lb (420 kg) |
| VEHICLE LOAD CAPACITY | 1200 lb (544 kg) | |
| BED LOAD CAPACITY | 800 lb (363 kg) | |
| OUTSIDE CLEARANCE CIRCLE | 25.5 ft (7.8 m) | |
| SPEED | 16.5 mph ± 0.5 mph (26.4 kph ± 0.8 kph) | 14 mph ± 0.5 mph (22.5 kph ± 0.8 kph) |

STEERING & SUSPENSION

| | | |
|----------------------|---|---|
| STEERING | Self-Compensating Rack and Pinion | |
| SUSPENSION | Leaf Springs w/ Hydraulic Shock Absorbers | |
| SERVICE BRAKE | Rear Wheel Mechanical Self-Adjusting Drum | |
| PARKING BRAKE | Automatic Electro-Magnetic | Self-Compensating, Single-Point Engagement |
| TIRES (FRONT & REAR) | 18 x 8.50 - 8 (4 Ply Rated) | |

ELITE LITHIUM POWERTRAIN

- Zero Maintenance Battery
- 5-Year Battery Warranty
- Lightweight Footprint
- Increased Efficiency
- Upgrade to 6.2 Triple Pack for Extended Range
- Automatic Park Brake
- Limited Slip Differential

OPTIONS & ACCESSORIES

- IntelliGauge™ (ELITE Only)
- Drop Side Rails
- Locking Glove Box
- Rear View Mirror
- Windshield
- Canopy
- Front Disc Brakes
- Turn Signal with Four-Way Flashers
- Strobe Lights
- Beacon Light Kit
- Dome and Work Lights
- LED Headlights
- LED Taillights/Brake Lights
- Hour Meter
- Full Cab
- Steel Cab and Doors
- Defroster
- Wheel Covers
- Additional Body Colors
- Premium Seating
- Limited Slip Differential

CUSHMAN.COM