

SHUTTLE™ 2+2

VERSATILITY COMMANDS THE DAY.

The newly redesigned Shuttle 2+2 is the ideal choice for transporting personnel and visitors. Comfortably seating up to four passengers with bench seats, the rear seat will also convert to a cargo deck. The Shuttle 2+2 is offered in your choice of a fuel-efficient 13.5-hp EFI gas engine or with an ELiTE lithium drivetrain powered by Samsung SDI lithium technology.

ELiTE
LITHIUM

ALL-NEW
IMPROVED STYLING

**NOW AVAILABLE
WITH**
ELiTE LITHIUM
POWERTRAIN

18" OR 20"
TIRE OPTIONS

2 OR 4-WHEEL
MECHANICAL BRAKE
OPTIONS



STANDARD FEATURES

- Rear-Facing Flip Seat
- Halogen Headlights
- 18" or 20" Tires
- 2-Wheel Mechanical Brakes
- E-Shield™ Frame
- Modular Canopy
- Premium Steering Wheel
- Side Body Color
- Multifunction Gauge (ELiTE only)
- Fuel and Oil Gauge (Gas only)

OPTIONS & ACCESSORIES

- 4-Wheel Mechanical Brakes
- Contoured Seats
- Limited Slip Differential
- LED Headlights, Taillights and Brake Lights
- Brush Guard
- Lockable Glove Box with Shelf and Molded Rubber Mats
- Fold-Down Windshield
- Weather Enclosure
- USB Outlet
- Rearview Mirror
- ELiTE Lithium 2.2, 4.2, or 6.2 Pack (ELiTE only)
- Rapid On-Board Charger (ELiTE only)

CUSHMAN.COM

SHUTTLE™ 2+2

SHUTTLE 2+2 ELITE		SHUTTLE 2+2 GAS		
18" TIRES		20" TIRES	18" TIRES	20" TIRES
BODY & CHASSIS				
FRAME		Welded Steel with E-Coat & DuraShield™ Powder Coat		
BODY & FINISH		Injection Molded TPO		
STANDARD COLOR		Patriot Blue		
DIMENSIONS				
OVERALL LENGTH		113 in (287 cm)		
OVERALL WIDTH		47 in (119 cm)		
OVERALL HEIGHT (W/ CANOPY)	76 in (193 cm)	80 in (203 cm)	76 in (193 cm)	80 in (203 cm)
OVERALL HEIGHT (W/O CANOPY)	48 in (122 cm)	52 in (132 cm)	48 in (122 cm)	52 in (132 cm)
WHEEL BASE		65.5 in (166 cm)		
WHEEL TRACK		37 in (94 cm) Front / 38 in (97 cm) Rear		
GROUND CLEARANCE	4.3 in (11 cm)	5.5 in (14 cm)	4.3 in (11 cm)	5.5 in (14 cm)
POWER				
POWER SOURCE		56.7V Li-Ion Battery		4-Cycle, 24.5 cu in (401cc)
VALVE TRAIN		N/A		Single Cylinder OHV
HORSEPOWER (KW)		11.7 hp (8.7 kW)		13.5 hp (10.1 kW)
ELECTRICAL SYSTEM		48V Primary, 12V Auxiliary		Starter/Generator, Solid State Regulator
BATTERY (QTY/TYPE)		2.2 Single, 56.7V Li-Ion Composite Module		One, 12V Maintenance Free
BATTERY CHARGER		56.7V, 350W Domestic Charger, 3M Charging Cord		N/A
KEY OR PEDAL START		Pedal		
AIR CLEANER		N/A		Industrial Rated Dry Filter
LUBRICATION		N/A		Pressurized Oil System
OIL FILTER		N/A		Spin-On
COOLING SYSTEM		N/A		Air Cooled
FUEL CAPACITY		N/A		5.96 Gallon (22.6 L) tank
DRIVE TRAIN		Motor Shaft Direct Drive		Continuously Variable Transmission (CVT)
TRANSAXLE		Differential w/ Helical Gears		
GEAR SELECTION		Dash Mount Forward-Neutral-Reverse / Key Switch		Forward - Reverse
REAR AXLE RATIO		16.99:1		11.47: 1 (Forward) / 14.35:1 (Reverse)
PERFORMANCE				
SEATING CAPACITY		4-Person		
WEIGHT W/O BATTERIES	743 lb (342 kg)	782 lb (351 kg)	872 lb (396 kg)	913 lb (414 kg)
CURB WEIGHT	790 lb (363 kg)	829 lb (372 kg)	902 (409 kg)	963 lb (437 kg)
VEHICLE LOAD CAPACITY		800 lb (363 kg)		
OUTSIDE CLEARANCE CIRCLE		18.9 ft (5.76 m)		
SPEED		16.5 mph ± 0.5 mph (26.5 kph ± 0.8 kph)		
STEERING & SUSPENSION				
STEERING		Self-Compensating Rack and Pinion		
SUSPENSION		Leaf Springs w/ Hydraulic Shock Absorbers		
SERVICE BRAKE		Dual Rear Wheel Mechanical Self-adjusting Drum		
PARKING BRAKE		Self-Compensating, Single-Point Engagement		
TIRES (FRONT & REAR)	Hole-N-One Tires	K399, 205/65-10, 6 Ply	Hole-N-One Tires	K399, 205/65-10, 6 Ply

Features and specifications of the vehicles are subject to change without notice. Vehicle as photographed may include options not included on base model. California state law prohibits the sale of Model Year 2024 and later gas-powered carts. ©2023 Textron Specialized Vehicles Inc. 60009-G9 (Rev. 12/2023)

