



SPRAYTEK XP™

PUSHES PERFECTION WITH PRECISION AND CONTROL.

The SprayTek XP offers an advanced low-profile tank, designed with high-pressure agitation, ensuring a properly mixed product. With a wide array of optional controls, including automatic rate control and powertrain options of a 32.5 hp gas engine or a 24.8 hp diesel engine, the SprayTek XP ensures you the longest-lasting ride on the fairway.

UP TO 20 FT.
SPRAY BOOMS

LOW PROFILE
TANK

PREMIUM
SUSPENSION
OPERATOR SEAT



SPRAYTEK XP™

XP175

XP300

POWER

TYPE	Diesel - Kubota D1105 Diesel, 3 Cylinder, 4-Cycle, Liquid Cooled
HORSEPOWER	Diesel - 24.8 hp (18.5 kW)
TORQUE	Diesel - 52.7 ft-lbs (71.5 N-m)
AIR CLEANER	Donaldson Dry Cartridge Type with Evacuator Valve
FUEL CAPACITY	7.0 gal. (26.5 L)

DRIVE TRAIN

SPEED	Diesel - Maximum Speed of 21 MPH. Optional 5th Gear Lock Out Available.
CLUTCH	7.1 in. (180 mm) Single Disc and Pressure Plate
DIFFERENTIAL LOCK	Electric Differential Lock on Rear Axle with Momentary Engagement Switch on Dash
MANUAL TRANSMISSION	Five Speed Manual Transmission with Low-Low (Creeper) First Gear; Synchronized in All Forward Gears; Two Speed Rear Axle

TIRES, BRAKING, & STEERING

FRONT TIRES	23 x 10.5 6-ply Ribbed (2WD) 23 x 10.5 - 14 6-Ply Treaded (4WD)
REAR TIRES	26 x 12 - 14 6-Ply Ultra Chevron tread
SERVICE BRAKES	Heavy-Duty Hydraulic Four-Wheel Disk Brakes with 10.7 in. (272 mm) Disk
PARKING BRAKES	Hand Lever Actuated Disk Brakes on Rear Wheels
STEERING	Hydrostatic Power Steering
FRONT SUSPENSION	Solid Axle with Heavy-Duty Multiple Leaf Springs and Shock Absorbers
REAR SUSPENSION	Solid Axle with Heavy-Duty Multiple Leaf Springs and Shock Absorbers

DIMENSIONS

LENGTH	164 in. (4.16 m)
HEIGHT	100 in. (2.54 m) (Nozzles 22 in Off Turf)
OPERATING WIDTH	15 ft. (4.6 m), 18.5 ft. (5.6 m) or 20 ft. (6.1 m) with 20 in. (51 cm) Nozzle Spacing
TRANSPORT WIDTH	69 in. (1.75 m) with 15 ft. or 18.5 ft. Booms Up / 87 in. (2.21 m) with 20 ft. Booms Up

SPRAYER COMPONENT

TANK	175 Gallons	300 Gallons
PUMP	64 GPM (224 LPM) at 93 PSI Maximum Flow Capacity	

STANDARD FEATURES

- Low Profile Tank with Increased Visibility and Stability
- Two-Post ROPS
- 2 Wheel Drive
- Premium Suspension Operator Seat
- Seatbelts
- Headlights
- Easy to Reach Console
- Fresh Water Wash Tank
- 12v Power Outlet
- Four-Wheel Disk Brakes
- Two-Speed Rear Axle
- Speed Control

OPTIONS & ACCESSORIES

- Full Line of Boom and Control Options
- Individual Nozzle Control
- GPS Mapping System
- Foam Marker System
- Manual or Electric Hose Reel
- Spray Gun
- Cleanload Chemical Eductor System
- Four-Post ROPS
- Canopy
- Cab
- Storage Box
- Work Light Kit
- CE Compliance Kit
- Tank Wash System
- Water Fill Meter Kit

CUSHMAN.COM

©2022 Textron Specialized Vehicles Inc. Features and specifications of the vehicles are subject to change without notice. Vehicle as photographed may include options not included on base model.

80002-G4 (Rev. 06/2022)

