

EXPERIENCE PROVEN PERFORMANCE.

The Hauler 800, now available with an ELiTE® lithium drivetrain powered by Samsung SDI battery technology or with a fuel-efficient 13.5 hp EFI gas engine, gives you the power to accomplish any task on your course. With a fully customizable cargo bed, highly functional dash and a broad range of accessories, Hauler 800 vehicles have everything you need to finish job after job.



8.4 CU FT

CARGO BED

900 LB

TOWING CAPACITY

800 LB

VEHICLE LOAD CAPACITY

2 PASSENGER

SEATING

ZERO MAINTENANCE

ELITE LITHIUM BATTERY





ELITE LITHIUM POWERTRAIN

- Zero Maintenance Battery
- 5-Year Battery Warranty
- Lightweight Footprint
- Increased Efficiency
- Upgrade to 6.2 Triple Pack for Extended Range
- Multifunction SOC/Speedometer Gauge
- Automatic Park Brake
- Limited Slip Differential

OPTIONS & ACCESSORIES

- 4-Wheel Mechanical Brakes
- Locking Glove Box
- Bed Dividers
- Floor Mount Attachment
- Windshield
- Canopy
- Electric Bed Lift
- Long-Handled Tool Holders
- Radio Holder
- Cargo Mesh Netting
- LED Headlights
- LED Taillights/Brake Lights
- Rearview Mirror
- USB Port
- Unique Key Switch
- Side Body Color
- Weather Enclosure
- ROPS-Certified Cab
- Ball Cage
- Hubcaps
- Rear Receiver Hitch
- Hour Meter
- Limited Slip Differential
- Rapid On-Board Charger
- Fuel/Oil Gauge

CUSHMAN.COM

HAULER 800

BODY & CHASSIS

FRAME	Welded Steel with E-Coat & DuraShield™ Powder Coat		
BODY & FINISH	Injection Molded TPO		
STANDARD COLOR	Forest Green		

HAULER 800 ELITE

HAULER 800 GAS

DIMENSIONS

110 in (279.4 cm)	

POWER

POWER TRAIN	56.7V Li-Ion Battery	4-Cycle, 24.5 cu in (401cc)	
VALVE TRAIN	N/A	Single Cylinder OHV	
HORSEPOWER (KW)	11.7 hp (8.7 kW) Peak	13.5 hp (10.1 kW)	
ELECTRICAL SYSTEM	48V Primary, 12V Auxiliary	Starter/Generator. Solid State Reg.	
BATTERY (QTY/TYPE)	2.2 Elite - Single Pack	One, 12V Maintenance Free	
KEY OR PEDAL START	Pedal		
AIR CLEANER	N/A	Replaceable Industrial Rated Dry Cartridge	
LUBRICATION	N/A	Pressurized Oil System	
OIL FILTER	N/A	Spin-On	
COOLING SYSTEM	N/A	Air Cooled	
FUEL CAPACITY	N/A	5.96 Gallon (22.6 L) tank	
DRIVE TRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission	
TRANSAXLE	Differential w/ Helical Gears		
GEAR SELECTION	Dash Mount Forward-Neutral- Reverse / Key Switch	Forward - Reverse	
REAR AXLE RATIO	16.99:1	11.47: 1 (Forward) 14.35:1 (Reverse)	

PERFORMANCE

SEATING CAPACITY	2-Person (Bench)		
WEIGHT W/O BATTERIES	753 lb (342 kg)	761 lb (345.2 kg)	
CURB WEIGHT	800 lb (363 kg)	791 lb (359 kg)	
VEHICLE LOAD CAPACITY	800 lb (362.9 kg)		
BED LOAD CAPACITY	400 lb (181.4 kg)		
TOWING CAPACITY	900 lb (408.2 kg)		
OUTSIDE CLEARANCE CIRCLE	18.9 ft (5.8 m)		
SPEED	16.5 mph ± 0.5 mph (26.5 kph ± 0.8 kph)	14.5 mph ± 0.5 mph (23.3 kph ± 0.8 kph)	

STEERING & SUSPENSION

STEERING	Self-Compensating Rack and Pinion		
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers		
SERVICE BRAKE	Rear Wheel Mechanical Self-Adjusting Drum		
PARKING BRAKE	Automatic Electro-Magnetic	Self-Compensating, Single-Point Engagement	

TIRES (FRONT & REAR) 18 x 8.5 -8 (6 Ply Tires)

