

DRIVE REVENUE WITH SUPERIOR TECHNOLOGY.

The Refresher Oasis was built for long days and busy events with its industry-leading can capacity and enough merchandising space for all your most popular items. With an ELiTE lithium drivetrain powered by Samsung SDI battery technology or a fuel-efficient 13.5 hp EFI gas engine, the Refresher Oasis pushes unparalleled customer service.

500 CAN

CAPACITY

12.1 SQ FT

COUNTER SPACE

6.7 CU FT

MERCHANDISE CABINET









ELITE LITHIUM POWERTRAIN

- Zero Maintenance
- 5-Year Battery Warranty
- Lightweight Footprint
- Increased Efficiency
- Upgrade to 6.2 Triple Pack for Extended Range
- Standard Limited Slip Differential
- Standard Automatic Park Brake
- Multifunction SOC/ Speedometer Gauge

OPTIONS & ACCESSORIES

- Trash/Recycle Bins
- Aluminum Canopy Frame
- Color Options Available for Canopy, Unit & Vehicle
- 3.0 Liter Airpots (2)
- Reversible Airpot Holder
- Humidor
- Consumable Ice Bin
- NSF Rated Ice Sink
- Unique Drainage
- Wheel Covers
- Turf Tires
- USB Outlet
- Glove Box Door and Shelf
- LED Headlights
- LED Taillights/Brake Lights
- Rapid On-Board Charger (ELiTE Only)

REFRESHER® OASIS™

ELITE LITHIUM

Welded Steel with E-Coat & DuraShield™ Powder Coat

EFI GAS

BODY & CHASSIS

FRAME

| BODY & FINISH | Injection Molded TPO, Painted (Front) | |
|---------------------------------------|---|--|
| STANDARD COLOR | Forest Green | |
| DIMENSIONS | | |
| OVERALL LENGTH | 117.0 in (297.18 cm) | |
| OVERALL WIDTH | 50.8 in (129.032 cm) | |
| OVERALL HEIGHT (NO CANOPY) | 47.4 in (120.40 cm) | |
| OVERALL HEIGHT (WITH CANOPY) | 73.3 in (186.18 cm) | |
| WHEEL BASE | 76 in (193.04 cm) | |
| FRONT WHEEL TRACK | 35 in (88.90 cm) | |
| REAR WHEEL TRACK | 38.5 in (97.79 cm) | |
| GROUND CLEARANCE | 4.5 in (11.43 cm) | |
| REFRESHER UNIT MATERIAL AND FINISH | 5000 Series Aluminum - Super Durable TGIC Polyester Powder Coating | |

POWER

| POWER SOURCE | 56.7 V Li-Ion Battery | 4 Cycle 24.5 cu in (401 cc) | |
|--------------------|---|---|--|
| MOTOR TYPE | AC Induction | N/A | |
| VALVE TRAIN | N/A | Single Cylinder OHV | |
| HORSEPOWER (KW) | 14.9 hp (11.1 kW) | 13.5 hp (10.1 kW) | |
| ELECTRICAL SYSTEM | 48V Primary, 12V Auxiliary | Starter/Generator, Solid-State Regulator | |
| BATTERY (QTY/TYPE) | 4.2 ELiTE - Twin Pack | One 12 Volt Maintenance Free | |
| BATTERY CHARGER | 811 Watt World Charger | N/A | |
| KEY OR PEDAL START | F | Pedal | |
| AIR CLEANER | N/A | Industrial Rated Dry Filter | |
| LUBRICATION | N/A | Pressurized Oil System | |
| OIL FILTER | N/A | Spin-On | |
| COOLING SYSTEM | N/A | Air Cooled | |
| FUEL CAPACITY | N/A | 6.65 Gallon (25 L) tank | |
| DRIVE TRAIN | Motor Shaft Direct Drive | Continuously Variable Transmission (CVT) | |
| TRANSAXLE | Limited-Slip Differential with Helical Gears | Differential with Helical Gears | |
| GEAR SELECTION | Forward-Neutral-Reverse | Forward-Reverse | |
| REAR AXLE RATIO | 16.99:1 | 16.53:1 (Forward) 16.81:1 (Reverse) | |
| | | | |

PERFORMANCE

| SEATING CAPACITY | 2-Person | | |
|----------------------------|---|----------------------|--|
| DRY WEIGHT (W/O BATTERIES) | 1017 lb (461 kg) | 1135 lb (514.83 kg) | |
| CURB WEIGHT | 1098 lb (498 kg) | 1175 lb (532.971 kg) | |
| VEHICLE LOAD CAPACITY | 1134 lb (514 kg) | 1066 lb (483 kg) | |
| OUTSIDE CLEARANCE CIRCLE | 21.5 ft (6.5 m) | | |
| SPEED | 11 mph \pm 0.5 mph (17.7 kph \pm 0.8 kph) | | |

STEERING & SUSPENSION

| STEERING | Self-Compensating Rack and Pinion | | |
|-----------------------|---|---|--|
| FRONT/REAR SUSPENSION | Leaf Springs with Hydraulic Shock Absorbers | | |
| SERVICE BRAKE | Rear Wheel Mechanical Self-Adjusting Drum | | |
| PARKING BRAKE | Automatic Electro-Magnetic | Self-Compensating, Single Point Engagement | |
| TIRES | 18 v 8 5-8 | | |

CUSHMAN.COM

