



TRUCKSTER[®] XD

CLASS-LEADING POWER AND PRODUCTIVITY.

The Truckster XD makes quick work of your hardest jobs with the industry's largest standard payload and your choice of Kubota gas or diesel engines. Built to operate in the toughest of conditions with a heavy gauge steel bed, the industry's highest approach angle, and largest ergonomic operator platform, your crew can count on the Truckster XD to handle tough tasks with ease.

INTEGRATED
STAKE POCKETS
AND TIE-DOWNS

HYDRAULIC
BED LIFT

3550 LB
LOAD CAPACITY

23.6 CU FT
HEAVY GAUGE
STEEL BED



OPTIONS & ACCESSORIES

- 66" Box
- 2" Receiver Hitch
- Canopy (Four-Post ROPS)
- Premium Suspension Seat (Operator and Passenger)
- Hi/Lo Hydraulics with Remote Ports
- Hydraulic PTO
- Throttle Control
- Turn Signals
- Cab (With or Without Doors)
- Heater
- Auto Tailgate
- Fifth Wheel Ball Hitch Including Electric Brake Controller
- Implement Lift
- Mirrors Left and Right
- Windshield for Four-Post ROPS
- Work Light Kit
- Backup Alarm
- Exhaust Spark Arrestor
- Fifth Gear Lock Out
- Storage Box
- Brush Guard

TRUCKSTER XD

GAS

DIESEL

BODY & CHASSIS

FRAME	Welded Steel with DuraShield™ Powder Coat
BODY & FINISH	Injection Molded
STANDARD COLOR	Orange, Forest Green

DIMENSIONS

OVERALL LENGTH (W/O BED)	132 in (335.3 cm)	133 in (337.8 cm)
OVERALL LENGTH (W/ BED)	136 in (345.4 cm)	
OVERALL WIDTH	65 in (165.1 cm)	
OVERALL HEIGHT	78 in (198.1 cm)	
WHEEL BASE	65 in (165.1 cm)	
FRONT WHEEL TRACK	49 in (124.5 cm)	
REAR WHEEL TRACK	52 in (132.1 cm)	
GROUND CLEARANCE	6.5 in (16.5 cm)	
CARGO BOX CAPACITY	23.6 cu ft (0.67 cu m)	

POWER

POWER SOURCE	32.5 hp Kubota Gas Engine	24.8 hp Kubota Diesel Engine
VALVE TRAIN	3-Cylinder, 4-Cycle Liquid Cooled EFI	3-Cylinder, 4-Cycle Liquid Cooled
HORSEPOWER (kW)	32.5 hp (24.2 kW)	24.8 hp (18.5 kW)
BATTERY (QTY/TYPE)	12 Volt Battery	
KEY OR PEDAL START	Key Start	
COOLING SYSTEM	Liquid Cooled	
FUEL CAPACITY	7.0 Gallons (26.5 L)	
DRIVE TRAIN	Motor Shaft Direct Drive	
GEAR SELECTION	Five Speed Manual (Optional 5th gear Lock Out Available.)	
REAR AXLE RATIO	High 14.2:1 / Low 45:1	

PERFORMANCE

SEATING CAPACITY	2-Person	
VEHICLE LOAD CAPACITY	3,550 lbs	
SPEED	23 mph	21 mph
TOWING CAPACITY	2,200 lbs, 3,500 lbs with Trailer Brakes	

STEERING & SUSPENSION

STEERING	Hydrostatic Power	
FRONT/REAR SUSPENSION	Solid Axle with Leaf Springs and Shock Absorbers	
SERVICE BRAKE	Heavy Duty Hydraulic Four Wheel Disk Brakes w/ 10.7 in-Disk	
PARKING BRAKE	Hand Lever Actuated Disk Brakes on Rear Wheels	
FRONT TIRES	23 x 10.5 - 14 6-Ply Ribbed (2WD) / 14 6-Ply Treaded (4WD)	
REAR TIRES	26 x 12 - 14 6-Ply Ultra Chevron Tread	

CUSHMAN.COM